

GROUNDTRAX

Ground Protection and Reinforcement



TRUCKPAVE™ cellular porous pavers

Product Data Sheet

Characteristics	TRUCKPAVE 80
Load-bearing capacity	Category SLW60. Vehicles up to 60t gross weight
Textured anti-skid surface	Available option
Connection type	Internal tongue & groove
Dimensions	80mm x 400mm x 600mm
Cell wall thickness	40mm nominal
Nominal internal cell dimensions	100mm x 100mm square
% open cell	55
Quantity per m ²	4.17 pavers
Quantity [m ²] per pallet	80 [19.18]
Nominal weight (kg) [kg/m ²]	9 [37.53]
Polymer	Recycled polyethylene
Colour	Grey (other colours available, subject to quantity)
Chemical resistance	Excellent
UV resistance	High
Toxicity	Non toxic

As part of its continual improvement process Groundtrax Systems Ltd reserve the right to change the properties listed on this data sheet without prior notice. Groundtrax Systems Ltd accept no responsibility for the accuracy of this data.



For more information, contact us
today or visit our website:

www.groundtrax.com

GROUNDTRAX
Ground Protection and Reinforcement
E-Mail: info@groundtrax.com | Telephone: 08456 800008 | Fax: 08456 800208